

### Cold (HOT\*) Water: Electric Powered – Stationary or Portable

The **CW Series** is a unique washer with hot water inlet capabilities that saves you time and money. Pressure clean thoroughly using your existing hot-water supply\* (up to 160°F standard or up to 190°F with an optional seal kit). The CW's versatile design allows it to be wall-mounted, floor mounted or portable depending on the cleaning task or application. The auto on/off feature allows you to clean with just one squeeze of the spray gun – no traveling back and forth to the unit to adjust the pressure or turn switches. The heavy-duty industrial components, stainless steel frame/cover and, belt driven pump provide a lifetime of continuous performance.

|                             |  |
|-----------------------------|--|
| <b>PRESSURE</b>             | 2100psi  |
| <b>FLOW CAPACITY</b>        | 4.0 gpm  |
| <b>POWER / ENGINE</b>       | 6.5 hp   |
| <b>VOLTS / PHASE / AMPS</b> | 230v - 1ph / 28amp   |
| <b>CONTROLS / SWITCHES</b>  | Hour meter, lighted on/off switch, GFCI & 35' cord included                      |
| <b>PUMP</b>                 | Cat Pump, oil bath, Triplex, ceramic plunger, brass head, stainless steel valves |
| <b>POWER DRIVE</b>          | V-Belt Drive, Low RPM -cooler, quieter, continuous duty performance              |
| <b>PRESSURE CONTROL</b>     | Adjustable pressure unloader, 24v adjustable timer with 7 to 300 second control  |
| <b>WATER SUPPLY</b>         | Pressure Feed from Garden Hose   |
| <b>WATER TEMPERATURE</b>    | Inlet water temp. from hot water source up to 190°F*                             |
| <b>SOAP INJECTION</b>       | Downstream soap injection included, inlet soap injection option available        |
| <b>PRESSURE HOSE</b>        | 3/8" x 50' 3000psi Wire Braided Hose   |
| <b>GUN / WAND</b>           | 48" molded insulator, adj. pressure wand with quick coupler                      |
| <b>NOZZLE</b>               | #5.5 (15°, 25°, 40°)   |
| <b>FRAME CONSTRUCTION</b>   | Stainless Steel frame, panels and removable cover                                |
| <b>WHEELS</b>               | Optional wheel/handle kit available  |
| <b>DIMENSIONS (LxWxH)</b>   | 28" x 21" x 14" (Dim with wheel kit: 39" x 29 1/2" x 36")                        |
| <b>NET WEIGHT</b>           | 155#   |

Specifications subject to change without notification and may vary due to ambient conditions.

\* CW Series accepts water from hot water heater or other hot water source up to 160°F standard, or up to 190°F with an optional seal kit



ETL Listed  
Certified to UL 1776  
Certified to  
CAN/CSA B140.11

#### Featuring:

- ✓ **Removable cover** for easy access and serviceability.
- ✓ **Unique integrated wall mount design** frees up valuable floor space
- ✓ **Cat V-belt driven pump** for long lasting performance
- ✓ **Auto ON/Off** with time delay shutdown saves time & effort.

#### Options...

Hot seal kit (HH3CP), Wall Mount Brackets Sideways Mount (ACW09), Wall mount hose reels (AR188), Wheel/handle kit (AHS15), Float tank/inlet soap injection option (WT0CW-not compatible with HH3CP), Multi station outlets (ACW20), Wall mount remote options (AEN35 or AEN22), stainless backing plate (HCW18)

TO: \_\_\_\_\_

COMMENTS: \_\_\_\_\_

YOUR PRICE: \_\_\_\_\_

DISTRIBUTED BY: \_\_\_\_\_



Shown with optional wheel kit and inlet soap/float tank