

### Steam / Hot / Cold Water Pressure Steamer – Natural Gas or LP Heated, Electric Motor

The **HN Pro Line® Series** is a heavy-duty stationary unit offering high output and instant cleaning power with adjustable temperature for various cleaning applications. The powder coated frame and stainless steel front panels and coil enclosure offer aesthetics and a balance of protection and accessibility to components. High torque / low RPM belt driven pump ensures years of worry free service with built in overheat protection if machine is left on. The automatic electronic ignition eliminates the need to manually light a pilot and increases the safety of the machine.

<b>PRESSURE</b>	3500 psi	
<b>FLOW CAPACITY</b>	4.3 gpm	
<b>OUTLET TEMP</b>	Adjustable, maximum 250°F	
<b>POWER/ENGINE</b>	10 hp	
<b>VOLTS/PHASE/AMPS</b>	<b>E3C</b> is dual rated 208v or 230v - 3 ph, 29a	<b>E4C</b> is 460v – 3ph, 13 amp
<b>CONTROLS/SWITCHES</b>	Lighted rocker switches, panel mounted soap control, adjustable thermostat	
<b>PUMP</b>	CAT Pump, triplex ceramic plunger	
<b>POWER DRIVE</b>	V-Belt drive with EZ Align™ pump rail	
<b>PRES. CONTROL</b>	By-Pass-Cool™ system / Safety relief valve and burst disc	
<b>WATER SUPPLY</b>	4 gallon float tank with double filtration and back flow prevention	
<b>PRESSURE HOSE</b>	3/8 x 50' steel wire braided / 250°F 4000 psi rated	
<b>GUN / WAND</b>	48" molded insulator wand, with quick coupler	
<b>SOAP INJECTION</b>	Full pressure chemical injection, precision stainless steel metering valve	
<b>NOZZLE</b>	#4.5 (15°, 40°), #3.5 (25° Steam)	
<b>BURNER COIL</b>	½" x 150' Schedule 80, ceramic insulation and stainless steel wrap and cap	
<b>BURNER/POWER</b>	Natural gas with auto ignition and 90 second safety lockout, cast iron ring, brass jets	
<b>BURNER INPUT</b>	440,000 BTU	
<b>CONSTRUCTION</b>	Powder coated support base and frame, stainless steel front panels and coil wrap	
<b>WHEELS</b>	Wheel kit option available for LP version	
<b>WEIGHT/DIM</b>	490#, 48"l x 21"w x 49"h	

\*Specifications subject to change without notification and may vary due to ambient conditions.  
 Not suitable for outdoor installation without protection from wind, overspray, rain, freezing

#### Featuring:

- ✓ **Open design** gives you full access to components
- ✓ **Adjustable Thermostat** with steam setting for various cleaning applications
- ✓ **By-Pass-Cool** system protects pump from overheating if left on after use
- ✓ **24 Volt Automatic Ignition** system on low emission natural gas burner

#### Options...

Hose reel (AR425, AR188) Draft diverter (BGD10), Downstream soap option (AC340), Multiple wash station shut-off (ACW20), Wind-up timer remote (AEN80), Full function remote (AENxx), LP conversion (BGV05), Wheel kit for LP version (AHSK5), Hour meter (AM603), Stainless frame upgrade (HS222), additional stainless panels-back and top (HS223)

TO: \_\_\_\_\_

COMMENTS: \_\_\_\_\_

YOUR PRICE: \_\_\_\_\_

DISTRIBUTED BY: \_\_\_\_\_

