

Steam / Hot / Cold Water: Diesel Heated, Electric Motor

The **HP Series** combines the cleaning power of high pressure and high water flow with the grease cutting effectiveness of hot water. Simply pull the trigger on the spray gun, and instantly the machine turns itself on and delivers high pressure cleaning power. The temperature can be adjusted to cold, hot, or steam for any cleaning application. The portable design and stainless steel construction offers years of trouble free service and cleaning performance anywhere electrical power is available.

PRESSURE	2200psi	
FLOW CAPACITY	4.3gpm	
OUTLET TEMP	Adjustable up to 250°F, 150°F rise	
POWER / ENGINE	7.5hp	
VOLTS/PHASE/AMPS	E3 is dual rated 208v or 230v – 3ph, 21amp	E4 is 460v, 3ph, 10a
CONTROLS/SWITCHES	Lighted on/off and lighted burner switch, thermostat, hour meter	
PUMP	Cat Pump, Oil Bath, Triplex Ceramic Plunger, Brass Head, Stainless Steel Valves	
POWER DRIVE	V Belt drive	
PRESSURE CONTROL	Adjustable pressure unloader and wand, safety relief valve, safety burst disc	
WATER SUPPLY	3-1/2 gal. float tank	
PRESSURE HOSE	3/8" x 50' 4000psi Rated	
SOAP INJECTION	Inlet chemical injection, injects at full pressure	
GUN / WAND	48" molded insulator, adj. pressure wand with quick coupler	
NOZZLE	#5.5 (15°, 40°) #4.5(25° Steam)	
BURNER COIL	1/2" Schedule 80 coil, Stainless Steel Enclosure	
BURNER / POWER	Oil Fired, Forced Draft, Automatic Ignition, Fuel Solenoid, Fuel Filter with Water Separator	
BURNER FUEL / CAP	Diesel fuel #1 or #2, Kerosene, Stove oil, JP8 fuel, 8 gallon capacity– 410,000 Btu input	
FRAME CONSTRUCTION	Stainless Steel frame, coil wrap and panels	
WHEELS	4) 13" tires installed	
NET WEIGHT / DIM	489#, 46"x29"x39"	500#, 46"x29"x39"

* Specifications subject to change without notification and may vary due to ambient conditions

Featuring:

- ✓ **Performance:** High heating ability and high flow increases cleaning speed and power
- ✓ **Portability:** Compact design for versatility and maneuverability.
- ✓ **Durability:** All Stainless steel construction and panels for lifetime corrosion resistance
- ✓ **Efficient:** High output diesel burner system offers clean burning and continuous hot water.
- ✓ **Convenient:** E.T.S. Electronic Trigger Start, 60 second delay Auto Off avoids risk of pump overheating and expensive thermal damage. Also features adjustable pressure at the wand

Options...

Hose Reel (AR189), Wet Sandblaster, Downstream injection kit



TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY: _____



HP shown with hose reel

